

**CLAIMS****What is claimed is:**

- 5           1.     In an implantable medical device for implant within a patient, the device having a plurality of sensors and a control unit for processing signals from the sensors, a method performed by the control unit comprising:
- 10                 receiving signals from the sensors representative of physiological parameters of the patient detected at sub-maximal exertion levels;
- estimating the ventilatory response of the patient at maximum exertion based on the signals detected at sub-maximal exertion levels; and
- 15                 controlling at least one function of the device based on the estimated ventilatory response.
2.     The method of claim 1:
- wherein the step of receiving signals representative of
- 20                 physiological parameters of the patient includes the step of receiving signals representative of Heart Rate, Arterial Oxygen Saturation, Right Ventricular O<sub>2</sub>, Stroke Volume, Tidal Volume, and Respiration Rate; and
- wherein the step of estimating ventilatory response includes
- 25                 the step of calculating
- $$VR = (Tidal\ Volume - Respiratory\ Rate) /$$
$$(\alpha \times (Arterial\ O_2\ Saturation - Right\ Ventricular\ O_2)$$
$$\times (Heart\ Rate) \times (Stroke\ Volume)).$$
- 30           3.     The method of claim 2 wherein the coefficient  $\alpha$  is about 1.14.

4. The method of claim 1:

wherein the step of receiving signals representative of physiological parameters of the patient includes the step of receiving signals representative of Heart Rate, Arterial Oxygen Saturation, Right Ventricular O<sub>2</sub>, Tidal Volume, and Respiration Rate; and

wherein the step of estimating ventilatory response includes the steps of inputting a Stroke Volume Constant and then calculating

$$\begin{aligned} \text{VR} = & (\text{Tidal Volume} - \text{Respiratory Rate}) / \\ & (\alpha \times (\text{Arterial O}_2 \text{ Saturation} - \text{Right Ventricular O}_2) \\ & \times (\text{Heart Rate}) \times (\text{Stroke Volume Constant})). \end{aligned}$$

5. The method of claim 4 wherein the Stroke Volume Constant is set to about 50 ml.

6. The method of claim 1:

wherein the step of receiving signals representative of physiological parameters of the patient includes the step of receiving signals representative of Heart Rate, Right Ventricular O<sub>2</sub>, Stroke Volume, Tidal Volume, and Respiration Rate; and

wherein the step of estimating ventilatory response includes the steps of inputting an Arterial Oxygen Saturation Constant and then calculating

$$\begin{aligned} \text{VR} = & (\text{Tidal Volume} - \text{Respiratory Rate}) / \\ & (\alpha \times (\text{Arterial O}_2 \text{ Saturation Constant} - \text{Right Ventricular O}_2) \\ & \times (\text{Heart Rate}) \times (\text{Stroke Volume})). \end{aligned}$$

7. The method of claim 6 wherein the Arterial O<sub>2</sub> Saturation Constant is about 0.95.

8. The method of claim 1 wherein the step of estimating ventilatory response for the patient includes the steps of:

receiving signals representative of ventilation amplitude, ventilation rate, and sinus rate; and

5 determining ventilatory response by multiplying the ventilation amplitude by the ventilation rate and correlating with the sinus rate.

9. The method of claim 1 wherein the step of estimating ventilatory response for the patient includes the steps of:

receiving signals representative of the current level of activity of the patient, sinus rate and minute ventilation; and

10 determining ventilatory response by dividing minute ventilation by the current level of activity of the patient and correlating with the sinus rate.

10. The method of claim 1 further including the step of determining a value representative of a risk of mortality to congestive heart failure based on the estimated ventilatory response.

11. The method of claim 10 wherein the step of controlling at least one function of the device includes the step of comparing the value representative of risk of mortality with a threshold value and, if it exceeds the threshold value, controlling a telemetry device to output a warning signal.

12. The method of claim 10 further including the step of also determining a value representative of a risk of mortality to congestive heart failure based on heart rate reserve as a function of the exertion level of the patient based on signals received from the sensors.

13. The method of claim 12 further including the step of combining the value representative of a risk of mortality determined based on ventilatory response with the value representative of a risk of mortality determined based on heart rate reserve as a function of the exertion level to yield a single congestive heart failure mortality risk metric.

14. The method of claim 1 wherein the step of controlling at least one function of the device includes the step of controlling a memory device to store the estimated ventilatory response as diagnostic information.

15. In an implantable medical device for implant within a patient, a system comprising:  
a plurality of physiological sensors; and  
a ventilatory response estimation unit operative to estimate the ventilatory response of the patient at maximum exertion based on the signals detected by the physiological sensors at sub-maximal exertion levels.

16. The system of claim 15 further wherein the ventilatory response estimation unit is part of a congestive heart failure (CHF) risk determination unit operative to process signals from the sensors and to determine the risk of mortality to CHF for the patient.

17. The system of claim 16 wherein the CHF risk determination unit also includes a heart rate reserve estimation unit operative to determine heart rate reserve as a function of exertion level and to determine the risk of mortality to CHF based on both heart rate reserve and ventilatory response.

18. The system of claim 16 wherein the CHF risk determination unit is further operative to compare the risk of mortality with a threshold risk level and to generate a warning signal if the risk of mortality exceeds the threshold risk level.

5

19. The system of claim 15 wherein plurality of sensors comprise:

a heart rate detector, an arterial oxygen saturation sensor, a right ventricular O<sub>2</sub> sensor, a stroke volume sensor, a tidal volume sensor, and a respiration rate sensor.

10

20. In an implantable medical device for implant within a patient, a system comprising:

means for determining that the patient is at a sub-maximal exertion level;

15

means for detecting one or more physiological parameters of the patient at the sub-maximal exertion level; and

means for estimating the ventilatory response of the patient at maximum exertion based on the signals detected at the sub-maximal exertion level.

20

21. The system of claim 20 further comprising means for determining a risk of mortality to congestive heart failure for the patient based on the estimated ventilatory response.

25

22. The system of claim 21 wherein the means for determining the risk of mortality to congestive heart failure comprises means for determining heart rate reserve for the patient as a function of exertion level and for determining the risk of mortality to CHF based on both heart rate reserve and ventilatory response.

30

23. The system of claim 22 wherein the means for determining the risk of mortality to congestive heart failure compares the value representative of risk of mortality with a threshold value and, if it exceeds the threshold value, generates a warning signal.

5

24. The system of claim 20 further comprising means for storing the estimated ventilatory response as diagnostic information.

10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995